



G
($\nabla \nabla \nabla$ = Ra0.8)



高週波硬度:HRC50°- 55°

Total Pitch Error
總齒距累積誤差

GT f/1000 ≤ 0.036mm

除非另有指定, 否則毫米為單位
Unless specify, unit is mm
去除毛邊與銳角
DEBUR AND SHARP CUTTING EDGES
表面加工 SURFACE FINISH:
公差 TOLERANCES:
線性 LINEAR:
角度 ANGLE:

高週波Hardness	有 Included	模數Module	8
四面研磨Sides Ground	有 Included	齒數Teeth No.	40T
齒研 Teeth Ground	有 Included	壓力角Pressure Angle	20°
染黑Blackening	無 Not included	右旋角Right Hand Angle	N/A
精度等級 Precision Grade	DIN 6級 DIN Grade 6	材質Material	SCM440

繪製 DRAWN BY	YUNG	Y Y C 群聚科技（廣東）有限公司 Qunju Technology (Guangdong) Co., Ltd
檢查 CHK' D		
核准 APPV' D		圖號 DWG NO: CSTGH08010-DIN6
日期 DATE : 2020. 5. 20		版次 A
比例 SCALE 1:2	重量WEIGHT:	圖頁 SHEET 1 OF 1